

Wireless Series Sonar Ready Adapter Listing

2009 MotorGuide®

MotorGuide
NEVER STOP.
motorguide.com

MotorGuide Wireless Sonar Ready Motors with Built-in Lowrance® 200 kHz Transducer and Temperature Sensor plug directly into Lowrance sonar units to maximize sonar performance. With a built-in transducer, motor installation is quick and easy with no transducer cables, wire-ties or hose clamps running down the shaft. Simply plug-in the 6-pin Lowrance Sonar connector coming out of the motor, connect your power cable and you are ready to go fishing. MotorGuide offers adapter cables for leading sonar brands including Garmin®, Humminbird®, Lowrance®, and Vexilar®, for additional transducer compatibility.*

* Note: Only works with 200 kHz units or only on 200 kHz side of dual frequency units.

Garmin® 6-Pin Adapter (without temp) #8M0029351

Garmin: Fishfinder 80*, Fishfinder 90, Fishfinder 100/BLUE, Fishfinder 120*, Fishfinder 140, Fishfinder 160/C, Fishfinder 240, Fishfinder 250/C, Fishfinder 320C, Fishfinder 340C, Fishfinder 400C,

GPSMAP 135, GPSMAP 168, GPSMAP 178/C, GPSMAP 185, GPSMAP 188/C, GPSMAP 198C, GPSMAP 235, GPSMAP 238, GPSMAP 298, GPSMAP 398, GPSMAP 498, GPSMAP 440/440S, GPSMAP 540/540S, GPSMAP 545/545S, GSD20, GSD21, GSD22

*With optional GARMIN part number 010-10145-00, sold separately.

Humminbird® 7-Pin Adapter (without temp) #8M0029352

Humminbird: 100SX/100PT, 105SX, 200 DX/PT, 405 SX/Plus, Angler 400+, HDR 600 In-Dash, HDR200, HDR600, LCR 100, LCR 400/ID/PT, LCRW, Legend 1000, Legend 2000, N525, Pro Angler 400SX, TCR-ID-10, TFX100 In-Dash, TFX128, TFX160, Tracker Pro 160, Trak Pro 128DX, Wide 100, Wide 128, Wide W, WPS60-ID In-Dash,

141c, 161, 323, 343c, 363, 383c, 300TX, 400TX, 917c, 931c, 937c, 957c, 981c SI, 987c SI, 717, 727, 737, 747c, 767, 777c2, 787c2, 797c, FishFinder 515, FishFinder 525, FishFinder 535/PT, FishFinder 565, FishFinder 575, FishFinder 580, FishFinder 585c, FishFinder 595c, HDR610, Legend 3000, Matrix 10, Matrix 12, Matrix 15, Matrix 17, Matrix 20, Matrix 25, Matrix 27, Matrix 35, Matrix 37, Matrix 55, Matrix 65, Matrix 67, Matrix 77C, Matrix 87C, Matrix 97,

Piranha 1, Piranha 2, Piranha 3, Piranha 4, Piranha 5, PiranhaMAX 10, PiranhaMAX 15, PiranhaMAX 20, PiranhaMAX 30, PiranhaMAX 210, PiranhaMAX 215, PiranhaMAX 220, PiranhaMAX 230, PiranhaMAX 240, TFX320, Wide 2000, Wide Eye, Wide Optic, Wide Panorama, Wide Paramount, Wide Portrait, Wide View, Wide Vision

Lowrance® 6-Pin Adapter (black) comes standard with motor

Lowrance: LCF-1440*, LST-3800*, M52i S/GPS, M56, M68C, M-68I s/Map, X-22A, X-25A, X-25B, X-37TX*, X-45, X-47/EX/TX*, X-50DS, X-67C, X-86DS, X-96

Eagle Models: Cuda 128*, Cuda 168/EX*, Cuda 240 GPS*, Cuda 242*, Cuda 250 S/Map*, FishEasy 2/2T*, FishEasy 240*, FishEasy 245DF/DS, FishEasy 250DF, FishEasy 320C*, FishElite 480, FishElite 500C, FishElite 502C iGPS, FishElite 640C, FishElite 642C iGPS, Fishmark 320*, FishMark 480*, FishMark 500C*, FishMark 640C*, FishStrike 1000C, FishStrike 2000C,

SeaChamp 1000C DF, SeaChamp 2000C DF, SeaCharter 500C DF, SeaCharter 502C DF/iGPS, SeaCharter 640C DF, SeaCharter 642C DF iGPS, SeaFinder 240DF, SeaFinder 245DF, SeaFinder 250DF, SeaFinder 320DF, SeaFinder 480DF, SeaFinder 500C DF, SeaFinder 640C DF

* Model not compatible with temperature sensor.

Lowrance® 7-Pin Adapter (blue/gray) #8M4000386

Lowrance: HDS-5, HDS-5x, HDS-7, HDS-8, HDS-10, LCX-104, LCX-110C, LCX-111C HD, LCX-112C, LCX-113C, LCX-15MT/CT/CI/C, LCX-16CT/CI, LCX-17M, LCX-18C*, LCX-19C*, LCX-20C, LCX-25C, LCX-26C HD, LCX-27C, LCX-28C HD, LCX-37C, LCX-38/LCX-38C HD, LCX-113C HD,

LMS-240, LMS-320/DF, LMS-330C, LMS-332C, LMS-334C iGPS, LMS-335C DF, LMS-337C DF, LMS-339C DF iGPS, LMS-480M, LMS-480M DF, LMS-520C, LMS-522C iGPS, LMS-525C DF, LMS-527C DF iGPS,

X-100C, X-102C, X-105C DF, X-107C DF, X-125, X-126DF, X-126C DF, X-135, X-136DF, X-136C DF, X-510C, X-515C DF, X-51, X-52, X-58 DF, X-59 DF, X-71, X-87, X-88 DF, X-91, X-97, X-98 DF

Eagle Models: FishEasy 2P*, Fishmark160, Fishmark240, TriFinder 2, FishEasy2(with gray connector), FishEasy 2T, SeaCharter 320 DF, SeaCharter 480 DF

* Model not compatible with temperature sensor.

Vexilar® 3-Pin Adapter (without temp) #8M0029350

Vexilar: FL-8, FL-8SLT, FL-8SE, FL-10, FL-12, FL-18, FL-20, CLC-200

