R SERIES

FRESHWATER
SALTWATER



SOMETIMES FISHERMEN CATCH FISH.

OTHER TIMES, FISHING CATCHES THEM.

MotorGuide®

MotorGuide®

R3

HAND-OPERATED \\ TRANSOM MOUNT \\ FRESHWATER \\ SALTWATER

A VERSATILE PERFORMER The R3 gets the job done for anglers looking for a transom mount motor that combines workhorse operation with the right level of refinement. Available in 5 forward/2 reverse or digital variable with smooth-running technology that ensures longer run time between battery charges. For even more flexibility, the motor head is reversible for bow-mount operation.

- **Classic twist tiller operation with extending handle**
- **Strong alloy mount with 7 locking positions**



R3 – FRESHWATER SPECIFICATIONS

MODEL	PART NUMBER	PEAK THRUST	SHAFT LENGTH	MAX AMP DRAW	VOLTS
R3-30FW 30” 03MT	940100170	30	30”	36	12
R3-40FW 36” 03MT	940100160	40	36”	42	12
R3-45FW 36” 09MT	940100150	45	36”	44	12
R3-55FW 36” 09MT	940100140	55	36”	49	12
R3-40FW 36” DIGITAL	940100200	40	36”	42	12
R3-45FW 36” DIGITAL	940100180	45	36”	44	12
R3-55FW 36” DIGITAL	940100190	55	36”	59	12
R3-55FW 42” DIGITAL	940100210	55	42”	59	12



R3 – SALTWATER SPECIFICATIONS

MODEL	PART NUMBER	PEAK THRUST	SHAFT LENGTH	MAX AMP DRAW	VOLTS
R3-45SW 36” DIGITAL 09MT	941000010	45	36”	44	12
R3-55SW 36” DIGITAL 09MT	941000020	55	36”	59	12

R5

HAND-OPERATED \\ TRANSOM MOUNT \\ FRESHWATER \\ SALTWATER

POWER THAT WORKS OVERTIME You can count on the new R5 transom mount to deliver thrust to move you effortlessly over long stretches. And with Digital Power Management technology extending the battery life, you can plan on spending more time fishing your favorite areas. Plus, MotorGuide invented saltwater-specific trolling motors, so we know a thing or two about protecting your investment from corrosion. Fish with more purpose and confidence than ever before with the all-new R5.

- **Classic twist tiller operation with extending handle**
- **Strong alloy mount features easy tilt/stow/deploy operation**
- **Saltwater models feature proprietary lower unit coatings that protect against corrosion**



R5 – FRESHWATER SPECIFICATIONS

MODEL	PART NUMBER	PEAK THRUST	SHAFT LENGTH	MAX AMP DRAW	VOLTS
R5-70FW 42” DIGITAL	940300030	70	42”	42	24
R5-80FW 42” DIGITAL	940300040	80	42”	56	24
R5-105FW 42” DIGITAL	940300050	105	42”	36	36



R5 – SALTWATER SPECIFICATIONS

MODEL	PART NUMBER	PEAK THRUST	SHAFT LENGTH	MAX AMP DRAW	VOLTS
R5-80SW 42” DIGITAL	941100010	80	42”	56	24
R5-105SW 50” DIGITAL	941100020	105	50”	36	36